



## Beschreibung

Revisionsstück zum Einbau in Rohre,  
Mit EPDM-Doppellippendichtung.

## ROD

Werkstoff: Stahlblech, sendzimirverzinkt,  
Ød1 80 bis 1250 mm.

## ROD2A:

Werkstoff: Edelstahl V2A 1.4301,  
Ød1 80 bis 1250 mm.

Ød <sub>1</sub> ND	Ausführung ROD					Gewicht (kg)	Ausführung ROD2A					Gewicht (kg)	
	L (mm)	l <sub>p</sub> (mm)	A (mm)	B (mm)			L <sub>1</sub> (mm)	l <sub>e</sub> (mm)	a (mm)	b (mm)	h (mm)		
80	250	40	180	x	80	1,2	250	40	180	x	80	100	0,8
100	250	40	180	x	80	1,3	250	40	180	x	100	110	0,9
125	250	40	180	x	80	1,4	250	40	180	x	125	112,5	1,1
140	270	40	200	x	100	1,5	250	40	180	x	140	130	1,2
150	270	40	200	x	100	1,5	250	40	180	x	150	135	1,3
160	270	40	200	x	100	1,6	250	40	180	x	160	140	1,4
180	270	40	200	x	100	1,7	250	40	180	x	180	150	1,5
200	270	40	200	x	100	2,1	270	40	200	x	180	160	1,7
224	270	40	200	x	100	2,3	270	40	200	x	180	172	1,9
250	270	60	200	x	100	2,5	270	40	200	x	180	185	2,0
280	270	60	200	x	100	2,7	270	40	200	x	180	200	2,2
300	270	60	200	x	100	2,8	270	40	200	x	180	210	2,3
315	270	60	200	x	100	2,9	270	40	200	x	180	217,5	3,2
355	270	60	200	x	100	3,2	270	70	200	x	180	237,5	3,4
400	400	80	300	x	200	6,1	400	70	300	x	250	260	5,7
450	400	80	300	x	200	6,5	400	70	300	x	250	285	6,2
500	400	80	300	x	200	7,0	400	70	300	x	250	310	6,8
560	500	80	400	x	300	10,7	500	70	400	x	300	340	9,5
600	500	80	400	x	300	11,2	500	70	400	x	300	360	10,1
630	500	80	400	x	300	13,6	500	70	400	x	300	375	13,1
710	500	100	400	x	300	15,5	500	100	400	x	300	415	14,4
800	500	100	400	x	300	16,9	500	100	400	x	300	460	16,0
900	500	100	400	x	300	20,0	500	100	400	x	300	510	17,7
1000	600	100	500	x	400	26,5	600	100	500	x	400	560	28,9
1120	600	120	500	x	400	30,1	600	100	500	x	400	620	31,9
1250	600	120	500	x	400	32,8	600	100	500	x	400	685	35,1