

To find reliable and safe leaks of gases and compressed air from 0°C to 50°C.:
Just spray on the suspected spot - when bubbles appear, you've found the leak:
easy, safe, quick, clean!

In cold and frosty conditions down to -15 °C, use Güpoflex Froststanding to test everything that has to be tight: Soldered, welded or screwed connections, fittings, hoses, pipes, valves, pressure vessels, etc.

Approved for use on oxygen installations.

Test results according to DIN EN 14291 ¹⁾:

Properties	Unit	Specified EN 14291	Güpoflex Froststanding
Surface tension	mN/m	< 30	25.93
Foam stability ²⁾	%	> 50	≥ 75
Corrosion attack on steel pipe sections	mg	< 20	2.7
pH valuet	-	6-8	6.790

¹⁾ acc. to control test procedure of the DVGW Research Unit at Engler-Bunte-Institute of Karlsruhe Institute of Technology, report from 28.04.2021.

²⁾ In-house laboratory.

Shelf life: see can imprint (5 years after production date).

All Güpoflex leak seekers are

- non-flammable
- biodegradable
- toxicologically harmless

For your safety at work, please request the current safety data sheet: email@guepo.de.

Compatible with sealing material according to EN 751-2 and lubricants according to EN 377.
According to EN 14291 on plastic and copper installations, rinse off after use.

You can obtain Güpoflex Leak-Finding Foam -15 °C, Art. 111 in:

- 400 ml: 12 aerosol cans /box
- 125 ml: 30 aerosol cans /box
- 25 ml: 8 or 120 aerosol cans /box

and as non-aerosol:

- from 500 ml to 1,000 l
- in trigger spray, canister, Politainer, drum and IBC

Temperature range:

From 0°C to +70 °C