

(B)

Page 1 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 26.07.2019 / 0018

Replacing version dated / version: 12.07.2019 / 0017

Valid from: 26.07.2019 PDF print date: 29.07.2019 Pro-Line Oel-Verlust-Stop 1 L

Art.: 5182

# Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

### Pro-Line Oel-Verlust-Stop 1 L

Art.: 5182

# 1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Additives

#### Uses advised against:

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet



LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany Phone:(+49) 0731-1420-0, Fax:(+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

#### Emergency information services / official advisory body:

---

#### Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

#### 2.2 Label elements

#### Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH210-Safety data sheet available on request.

#### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

Product can compose a film on the water surface, which can prevent oxygen exchange.

#### **SECTION 3: Composition/information on ingredients**



Page 2 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 26.07.2019 / 0018

Replacing version dated / version: 12.07.2019 / 0017

Valid from: 26.07.2019 PDF print date: 29.07.2019 Pro-Line Oel-Verlust-Stop 1 L

Art.: 5182

#### 3.1 Substance

# n.a. **3.2 Mixture**

2-butoxyethyl acetate	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119475112-47-XXXX
Index	607-038-00-2
EINECS, ELINCS, NLP	203-933-3
CAS	112-07-2
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H302
	Acute Tox. 4, H312
	Acute Tox. 4. H332

Isotridecanol, ethoxylated	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	500-241-6 (NLP)
CAS	69011-36-5
content %	3-<5
Classification according to Regulation (EC) 1272/2008 (CLP)	Aquatic Chronic 3, H412

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eve contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the eves

Product removes fat.

Drying of the skin.

Dermatitis (skin inflammation)

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

#### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media



Page 3 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 26.07.2019 / 0018

Replacing version dated / version: 12.07.2019 / 0017

Valid from: 26.07.2019 PDF print date: 29.07.2019 Pro-Line Oel-Verlust-Stop 1 L

Art.: 5182

#### Suitable extinguishing media

CO2 Foam

Dry extinguisher

#### Unsuitable extinguishing media

High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Hydrocarbons

Toxic pyrolysis products.

Hot product gives off combustible vapours.

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Remove possible causes of ignition - do not smoke.

Avoid formation of oil mist.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

#### 6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

#### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

#### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

#### **SECTION 7: Handling and storage**

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

#### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes or skin.

Do not heat to temperatures close to flash point.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Do not carry cleaning cloths soaked in product in trouser pockets.

Observe directions on label and instructions for use.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### 7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.



Page 4 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 26.07.2019 / 0018

Replacing version dated / version: 12.07.2019 / 0017

Valid from: 26.07.2019 PDF print date: 29.07.2019 Pro-Line Oel-Verlust-Stop 1 L

Art.: 5182

Store product closed and only in original packing.

Solvent resistant floor

Do not store with oxidizing agents.

Protect from direct sunlight and warming.

#### 7.3 Specific end use(s)

No information available at present.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

Chemical Name	2-butoxyethyl ac	etate			Content %:1-<10
WEL-TWA: 20 ppm (133 mg/m3) (	(WEL, EU)	WEL-STEL: 50 ppm (33			
Monitoring procedures:			nische 3), DFG (E) (Solvent m	ixtures 3)	- 1998, 2002 - EU
	-	project BC/CEN/ENTR/000/2	002-16 card 33-3 (2004)		
BMGV:			Other information: S	Sk (WEL)	
® Chemical Name	Oil mist, mineral				Content %:
WEL-TWA: 5 mg/m3 (Mineral oil, e	excluding metal	WEL-STEL:			
working fluids, ACGIH)					
Monitoring procedures:	-	Draeger - Oil 10/a-P (67 28 3	371)		
	-	Draeger - Oil Mist 1/a (67 33	031)		
BMGV:		-	Other information: -	-	

2-butoxyethyl acetate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,304	mg/l	
	Environment - marine		PNEC	0,0304	mg/l	
	Environment - sediment, freshwater		PNEC	2,03	mg/kg dw	
	Environment - sediment, marine		PNEC	0,203	mg/kg dw	
Consumer	Human - oral	Long term, systemic effects	DNEL	4,3	mg/kg bw/d	
Consumer	Human - dermal	Long term, systemic effects	DNEL	36	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	67	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	102	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	133	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	333	mg/m3	

<sup>®</sup> WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

#### 8.2 Exposure controls

#### 8.2.1 Appropriate engineering controls

<sup>(8) =</sup> Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

<sup>(8) =</sup> Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

<sup>\*\* =</sup> The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.



Page 5 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 26.07.2019 / 0018

Replacing version dated / version: 12.07.2019 / 0017

Valid from: 26.07.2019 PDF print date: 29.07.2019 Pro-Line Oel-Verlust-Stop 1 L

Art.: 5182

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

#### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

If applicable

Protective nitrile gloves (EN 374).

Permeation time (penetration time) in minutes:

>480

Minimum layer thickness in mm:

0,4

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Filter A2 P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

#### 8.2.3 Environmental exposure controls

No information available at present.

## **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state:

Colour:

Odour:

Pastelike, Liquid
Yellow, Clear
Characteristic



Page 6 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 26.07.2019 / 0018

Replacing version dated / version: 12.07.2019 / 0017

Valid from: 26.07.2019 PDF print date: 29.07.2019 Pro-Line Oel-Verlust-Stop 1 L

Art.: 5182

Odour threshold: Not determined

pH-value: n.a.

Melting point/freezing point:

Not determined Initial boiling point and boiling range:

Not determined

>100 °C Flash point: Evaporation rate: Not determined Flammability (solid, gas): Not determined Lower explosive limit: Not determined Upper explosive limit: Not determined Vapour pressure: Not determined Vapour density (air = 1): Not determined Density: 0,896 g/ml (20°C) Bulk density: Not determined Solubility(ies): Not determined

Water solubility:
Partition coefficient (n-octanol/water):
Auto-ignition temperature:
Decomposition temperature:
Viscosity:
Insoluble
Not determined
Not determined
Not determined
1299 mPas (20°C)

Explosive properties: Not determined

Oxidising properties: No

9.2 Other information

Miscibility:

Fat solubility / solvent:

Conductivity:

Not determined

Not determined

Not determined

Surface tension:

Not determined

Not determined

Not determined

Not determined

#### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

The product has not been tested.

#### 10.2 Chemical stability

Stable with proper storage and handling.

#### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

#### 10.4 Conditions to avoid

Strong heat

#### 10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

#### 10.6 Hazardous decomposition products

No decomposition when used as directed.

### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Pro-Line Oel-Verlust-Stop 1 L						
Art.: 5182						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value,
						Vapours
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.



B)

Page 7 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 26.07.2019 / 0018

Replacing version dated / version: 12.07.2019 / 0017

Valid from: 26.07.2019 PDF print date: 29.07.2019 Pro-Line Oel-Verlust-Stop 1 L

Art.: 5182

Carcinogenicity:		n.d.a.	
Reproductive toxicity:		n.d.a.	
Specific target organ toxicity -		n.d.a.	
single exposure (STOT-SE):			
Specific target organ toxicity -		n.d.a.	
repeated exposure (STOT-RE):			
Aspiration hazard:		n.d.a.	
Symptoms:		n.d.a.	
Other information:		Classificati	on
		according t	0
		calculation	
		procedure.	

2-butoxyethyl acetate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1880	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by dermal route:	LD50	1500	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LD50	>2,7	mg/l/4h	Rat		Mist
Skin corrosion/irritation:				Rabbit		Not irritant
Serious eye damage/irritation:				Rabbit		Not irritant
Respiratory or skin						Not sensitizising
sensitisation:						
Symptoms:						breathing
						difficulties,
						headaches,
						gastrointestinal
						disturbances,
						mucous
						membrane
						irritation,
						dizziness,
						nausea and
						vomiting.

Isotridecanol, ethoxylated						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	
					Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant,
					Dermal	Analogous
					Irritation/Corrosion)	conclusion
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin contact)
sensitisation:					Sensitisation)	
Germ cell mutagenicity:				Mammalian	OECD 476 (In Vitro	Negative
					Mammalian Cell Gene	
					Mutation Test)	

## **SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).

Pro-Line Oel-Verlust-Stop 1 L

Art.: 5182							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.



Page 8 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 26.07.2019 / 0018

Replacing version dated / version: 12.07.2019 / 0017

Valid from: 26.07.2019 PDF print date: 29.07.2019 Pro-Line Oel-Verlust-Stop 1 L Art.: 5182

12.2. Persistence and degradability:	Isolate as much as possible with an oil separator.
12.3. Bioaccumulative potential:	n.d.a.
12.4. Mobility in soil:	n.d.a.
12.5. Results of PBT	n.d.a.
and vPvB assessment	
12.6. Other adverse	n.d.a.
effects:	
Other information:	According to the recipe, contains no AOX.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	28	mg/l	Oncorhynchus	OECD 203 (Fish,	
					mykiss	Acute Toxicity	
						Test)	
12.1. Toxicity to daphnia:		48h	37	mg/l	Daphnia pulex	DIN 38412 T.11	
12.3. Bioaccumulative potential:	BCF		<100				Low
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Pseudokirchneriell a subcapitata	ISO/DIS 8692	References
12.2. Persistence and		28d	88	%	·	OECD 301 C	
degradability:						(Ready	
						Biodegradability -	
						Modified MITI	
1000				0/		Test (I))	B: 1 111
12.2. Persistence and		28d	>70	%		OECD 301 F	Biodegradable
degradability:						(Ready	
						Biodegradability -	
						Manometric	
12.3. Bioaccumulative	Log Dow		1,51			Respirometry Test) OECD 107	
potential:	Log Pow		1,51			(Partition	
potential.						Coefficient (n-	
						octanol/water) -	
						Shake Flask	
						Method)	
12.5. Results of PBT						ivicatiou)	No PBT
and vPvB assessment							substance, No
							vPvB substanc
12.4. Mobility in soil:	Koc		26-224				HighEstimated
Toxicity to bacteria:	EC50	17h	720	mg/l	Pseudomonas	DIN 38412 T.8	<u> </u>
•					putida		

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
2.1. Toxicity to fish:	LC50	96h	5,18	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
2.1. Toxicity to fish:	LC50	96h	2,5	mg/l	Brachydanio rerio	Regulation (EC) 440/2008 C.1 (ACUTE TOXICITY FOR FISH)	
12.1. Toxicity to daphnia:	EC50	48h	1,5	mg/l	Daphnia magna	Regulation (EC) 440/2008 C.2 (DAPHNIA SP. ACUTE IMMOBILISATION TEST)	



Page 9 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 26.07.2019 / 0018

Replacing version dated / version: 12.07.2019 / 0017

Valid from: 26.07.2019 PDF print date: 29.07.2019 Pro-Line Oel-Verlust-Stop 1 L

Art.: 5182

12.1. Toxicity to daph	nnia: EC20	21d	0,74	mg/l	Daphnia magna	QSAR	
12.1. Toxicity to alga	e: EC50	72h	2,5	mg/l	Desmodesmus subspicatus	Regulation (EC) 440/2008 C.3 (FRESHWATER ALGAE AND CYANOBACTERI A, GROWTH INHIBITION TEST)	
Toxicity to bacteria:	EC50	3h	140	mg/l	activated sludge		EC 88/302

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Implement substance recycling.

E.g. suitable incineration plant.

#### For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

#### **SECTION 14: Transport information**

#### **General statements**

14.1. UN number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.Classification code:n.a.LQ:n.a.

14.5. Environmental hazards:

Not applicable

Tunnel restriction code:

#### Transport by sea (IMDG-code)

14.2. UN proper shipping name:
14.3. Transport hazard class(es):
14.4. Packing group:
n.a.

Marine Pollutant:

14.5. Environmental hazards:

n.a

Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):n.a.14.4. Packing group:n.a.

14.5. Environmental hazards: Not applicable

#### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.



Page 10 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 26.07.2019 / 0018

Replacing version dated / version: 12.07.2019 / 0017

Valid from: 26.07.2019 PDF print date: 29.07.2019 Pro-Line Oel-Verlust-Stop 1 L

Art.: 5182

#### **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)! General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC):

9 %

#### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

#### **SECTION 16: Other information**

Revised sections:

2, 3, 4, 7, 11, 12, 16

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H412 Harmful to aquatic life with long lasting effects.

Acute Tox. — Acute toxicity - oral

Acute Tox. — Acute toxicity - dermal Acute Tox. — Acute toxicity - inhalation

Aguatic Chronic — Hazardous to the aguatic environment - chronic

#### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

**BSEF** The International Bromine Council

body weight bw

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

Derived No Effect Level DNEL

dry weight dw

for example (abbreviation of Latin 'exempli gratia'), for instance e.g.

ΕČ **European Community** ECHA European Chemicals Agency **EEC** European Economic Community

**EINECS** European Inventory of Existing Commercial Chemical Substances



Page 11 of 11

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 26.07.2019 / 0018

Replacing version dated / version: 12.07.2019 / 0017

Valid from: 26.07.2019 PDF print date: 29.07.2019 Pro-Line Oel-Verlust-Stop 1 L

Art.: 5182

**ELINCS** European List of Notified Chemical Substances

ΕN European Norms

**FPA** United States Environmental Protection Agency (United States of America)

etc. et cetera

ΕU **European Union** 

**EVAL** Ethylene-vinyl alcohol copolymer

Fax number Fax. general gen.

GHS Globally Harmonized System of Classification and Labelling of Chemicals

**GWP** Global warming potential

**IARC** International Agency for Research on Cancer International Air Transport Association IATA IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

including, inclusive incl

**IUCLID International Uniform Chemical Information Database** 

LQ **Limited Quantities** 

MARPOL International Convention for the Prevention of Marine Pollution from Ships

not applicable n.a. not available n.av. not checked n.c. no data available n.d.a.

OECD Organisation for Economic Co-operation and Development

org. organic

persistent, bioaccumulative and toxic PBT

PΕ Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million

**PVC** Polyvinylchloride

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List

Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Telephone Tel.

**UN RTDG** United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

very persistent and very bioaccumulative vPvB

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

# These statements were made by: Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

 $\ensuremath{\mathbb{G}}$  by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.