



CERT

DVGW type examination certificate

DVGW-Baumusterprüfzertifikat

DG-4350CU0372

Registration Number
Registriernummer

Field of Application <i>Anwendungsbereich</i>	products of gas supply <i>Produkte der Gasversorgung</i>
Owner of Certificate <i>Zertifikatinhaber</i>	TECO s.r.l. Via Sandro Pertini 39/41, I-25050 Provaglio d'Iseo (BS)
Distributor <i>Vertreiber</i>	TECO s.r.l. Via Sandro Pertini 39/41, I-25050 Provaglio d'Iseo (BS)
Product Category <i>Produktart</i>	gas fittings: Meter screwing (4350)
Product Description <i>Produktbezeichnung</i>	meter screwing optional with integrated straight pattern ball valve with or without thermally triggered shut-off valve or with or without excess flow valve
Model <i>Modell</i>	KM3...
Test Reports <i>Prüfberichte</i>	supplement test: 20-00309-312 from 23.07.2020 (EBI)
Test Basis <i>Prüfgrundlagen</i>	DIN 3376-1 (01.02.2005)- partially (see remarks)



7008-04-A-DE

Date of Expiry / File No. 25.09.2022 / 20-0413-GNR
Ablaufdatum / Aktenzeichen

07.05.2021 Rie A-1/2

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle



DVGW CERT GmbH
Zertifizierungsstelle
Josef-Wirmer-Str. 1-3
53123 Bonn
Tel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993
www.dvgw-cert.com
info@dvgw-cert.com

Type <i>Typ</i>	Technical Data <i>Technische Daten</i>	Remarks <i>Bemerkungen</i>
KM3-VF-25	nominal pressure rating: MOP 5/C0,1 nominal diameter: DN 25	with integrated ball valve
KM3-PP-25	nominal pressure rating: MOP 5/B0,1 nominal diameter: DN 25	with integrated ball valve
KM3-VT-25	nominal pressure rating: MOP 5/C5 nominal diameter: DN 25	with integrated ball valve with thermally triggered shut-off valve
KM3-PT-25	nominal pressure rating: MOP 5/C1 nominal diameter: DN 25	with integrated ball valve with thermally triggered shut-off valve
KM3-VG-25	nominal pressure rating: MOP 5/C0,1 nominal diameter: DN 25	with integrated ball valve with excess flow valve
KM3-PG-25	max. operating pressure: 0,015...0,1 bar nominal pressure rating: MOP 5/B0,1 nominal diameter: DN 25	with integrated ball valve with excess flow valve
KM3-RC-25	max. operating pressure: 0,015...0,1 bar nominal pressure rating: MOP 1 nominal diameter: DN 25	
KM3-PC-25	nominal pressure rating: MOP 5/C1 nominal diameter: DN 25	

Type Variation <i>Ausführungsvariante</i>	Explanations <i>Erläuterungen</i>
KM3-VF-25; KM3-VT-25; KM3-RC-25; KM3-VG-25	connection to the gas pipe: female thread Rp 1 according to DIN EN 10226-1
KM3-PP-25; KM3-PT-25; KM3-PC-25; KM3-PG-25	connection to the gas pipe: pressing joint according to DVGW G 5614

certified Components**zertifizierte Bauteile / Werkstoffe**

Registr. No. <i>Registrier-Nr.</i>	Component <i>Bauteil (Produktart)</i>	Model/Type <i>Modell/Typ</i>	Manufacturer <i>Hersteller</i>
DG-4360BP0116	Gas flow governor	GST.../GST/L 2; GST/EFV; GST L2-V2	TECO s.r.l.
DG-4550BU0317	Compression joint for metallic gas pipes	G-Press/RP 15 V1 CW	TECO s.r.l.
DG-4312CN0154	Shut-off valve <= MOP 5	G2 CM ST...; G2 MB ST...; G2 CM SQ.../G2 CM ST LE FF V1 STD; G2 CM ST LE FF V1 TAS; G2 MB ST OC V2 STD	TECO s.r.l.

Hints of Utilization / Remarks**Verwendungshinweise / Bemerkungen**

The testing and certification was carried out regarding the dimensions (type of construction) partially according to DIN 3376-1.

